
Multi-Hop Reasoning for Question Answering with Hyperbolic Representations




Simon Welz¹, Lucie Flek^{1,2}, Akbar Karimi^{1,2}

¹Bonn-Aachen International Center for Information Technology, University of Bonn, Germany ²Lamarr Institute for Machine Learning and Artificial Intelligence, Germany







Motivation

Hyperbolic Models fit hierarchical structures more naturally:

- Exponential Growth
- Distances modelled according to tree-structure


Research Gaps

- Lack of controlled comparison between hyperbolic and Euclidean spaces
- Curvature analysis in hyperbolic space is underexplored

Parse then Hop

Question: Which country is the composer of song Cloudburst from? Relevant (Cloudburst, composer, Eric Whitacre) Knowledge (Eric Whitacre, country of citizenship, American)

Knowledge Integration




Main Results


Stage	Space	2WikiHop	MetaQA	MLPQ	PQ
	Euclidean	44.36	22.92	81.03	18.28
Hopping	Hyperbolic	46.93	28.33	82.60	29.03
Darcing	Euclidean	88.60	95.51	97.08	100
Parsing	Hyperbolic	89.34	95.65	97.14	100

Dataset Hierarchy

More hierarchy leads to more improvement.




Curvature Analysis



Curvature initialization is crucial for performance.

Embedding Space

Hyperbolic embeddings are more spread out than Euclidean embeddings.



Takeaways

- Hyperbolic space outperforms Euclidean one in multihop reasoning.
- Hierarchical datasets benefit more from hyperbolic representations.
- Curvature initialization is critical for performance.

Partner institutions:











Institutionally funded by:



